

Условное обозначение	диаметр	давление	Размеры			компенсирующая способность		Расчетный вес	жёсткость	эффективная площадь
	DN	PN	dr	s	L	Δ	±λ		C <sub>к</sub>	S <sub>эф</sub>
	мм mm	Бар bar	мм mm	мм mm	мм mm	мм mm	мм mm	кг kg	N/мм N/mm	см <sup>2</sup> cm <sup>2</sup>
KCO 40-16-50	40	16	48,3	3,2	240	50	25	0,75	120,94	22,35
KCO 50-16-50	50	16	57	3,5	240	50	25	1,07	153,93	32,83
KCO 65-16-60	65	16	76	4,0	240	60	30	1,5	288,94	59,99
KCO 80-16-60	80	16	89	4,0	250	60	30	2,1	219	82,52
KCO 80-16-70	80	16	89	4,0	415	70	35	3,4	203,36	82,52
KCO 100-16-60	100	16	108	4,0	270	60	30	2,5	203,85	116,9
KCO 100-16-100	100	16	108	4,0	408	100	50	5	188,17	116,9
KCO 125-16-60	125	16	133	5,0	250	60	30	2,6	290,92	154,38
KCO 125-16-100	125	16	133	5,0	428	100	50	5	207,8	154,38
KCO 150-16-60	150	16	159	5,0	270	60	30	3,8	357,43	232,89
KCO 150-16-100	150	16	159	5,0	485	100	50	7,4	206,93	232,89
KCO 200-16-80	200	16	219	8,0	300	80	40	9,2	720,29	456,92
KCO 200-16-100	200	16	219	8,0	475	100	50	15,3	523,85	456,92
KCO 200-16-160	200	16	219	8,0	560	160	80	17,2	384,16	456,92
KCO 250-16-80	250	16	273	8,0	315	80	40	12,6	663,97	683,49
KCO 250-16-100	250	16	273	8,0	445	100	50	18,4	531,18	683,49
KCO 250-16-160	250	16	273	8,0	612	160	80	25,2	379,41	683,49
KCO 300-16-80	300	16	325	8,0	320	80	40	13,8	871,67	959,91
KCO 300-16-100	300	16	325	8,0	475	100	50	21,5	653,75	959,91
KCO 300-16-180	300	16	325	8,0	632	180	90	26,2	402,31	959,91
KCO 350-16-80	350	16	377	7,0	440	80	40	21,37	723,51	1234,74
KCO 350-16-100	350	16	377	7,0	505	100	50	24	578,81	1234,74
KCO 350-16-180	350	16	377	7,0	640	180	90	29,2	413,44	1234,74
KCO 400-16-80	400	16	426	9,0	390	80	40	28,7	1779,51	1622,40
KCO 400-16-100	400	16	426	9,0	545	100	50	38,3	1067,71	1622,40
KCO 400-16-190	400	16	426	9,0	668	190	95	47,3	889,75	1622,40
KCO 450-16-100	450	16	478	8,0	602	100	50	43,4	1157,73	2038,02
KCO 450-16-180	450	16	478	8,0	675	180	90	51	992,04	2038,02
KCO 500-16-80	500	16	530	8,0	440	80	40	34,4	1456,69	2463,01
KCO 500-16-100	500	16	530	8,0	610	100	50	45,1	1165,35	2463,01
KCO 500-16-200	500	16	530	8,0	682	200	100	53,9	1059,41	2463,01
KCO 600-16-200	600	16	630	10,0	713	200	100	91	2122,48	3433,65
KCO 700-16-210	700	16	720	10,0	710	210	105	116	1837,73	4484,08
KCO 800-16-210	800	16	820	12,0	743	210	105	140	2237,86	5787,21
KCO 900-16-210	900	16	920	14,0	719	210	105	184	2606,63	7241,25
KCO 1000-16-220	1000	16	1020	14,0	742	220	110	216	3321,89	8841,39
KCO 1200-16-220	1200	16	1220	16,0	742	220	110	300	3271,21	12522,48